



Oil Removal Filters

Oil content of the compressed air can be controlled to 0.003mgs/m³ through our oil removal filters. These free standing units are housed in a lifting frame for ease of transport and protection on site.

The volume range is 25m³/min (875 cfm) to 92m³/min (3258 cfm) with a pressure range from 10 bar (150 psi) to 40 bar (580 psi). The housing material used determines both pressure and output.

Technical Specifications

Oil Removal Filters

Performance

Model	Oil Removal Filter		
Volume Dependant on Working Pressure	875 cfm @ 150 psi 25m ³ /min @ 10 bar	2066 cfm @ 365 psi 59m ³ /min @ 25 bar	3258 cfm @ 580 psi 92m ³ /min @ 40 bar
Residual Oil Content @ 20°C	0.003mgs/m ³		
Discharge Temperature	Ambient +10°C		
Inlet / Outlet Connections	DN50 / Fig 100		

Dimensions

	Metric	Imperial
Overall Length	1600mm	63"
Overall Width	1350mm	53"
Overall Height	1465mm	58"

N.B. Dimensions are for guidance only; please contact your local Airpac Rentals office for individual asset details

E. & O.E.

© Airpac Rentals 2021
A division of Vp plc



Airpac Rentals UK is certified to
BS EN ISO 9001:2015 & BS EN ISO 14001:2015



Supplier No. 10044388

UK & Europe
e: airpac.europe@vpplc.com

Asia
e: airpac.asia@vpplc.com

Australia
e: airpac.australia@vpplc.com

Middle East & Africa
e: airpac.mea@vpplc.com

Americas
e: airpac.americas@vpplc.com

25.11.21